

DECLARATION OF PERFORMANCE

SalzCBasic-CPR-2019/05/31-GB



PRODUCT

Product type	Slow heat release appliance
Type designation	Salzburg C Basic
Product identification	See product instruction manual
Intended area of use	Heating of rooms in residential buildings
Fuel	Wood

MANUFACTURER

Name	Nordpeis AS
Adress	Gjellebekkstubben 11 3420 Lierskogen, Norway

CHECKS

According to AVCP	System 3
Standard	EN 15250:2007
Test institute	Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625 has checked declared performance and issued test report no. RRF- 50 15 3896

DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1 WT	EN 15250:2007
Minimum distances to combustible material	50 mm rear 50 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion: Carbon monoxide at 13% O ₂ Oxygen nitride NO _x at 13% O ₂ Organic Gaseous Carbon at 13% O ₂ Particulate Matter at 13 O ₂	CO = 0,100 % Vol NO _x = 115 mg / m ³ OGC = 128 mg / m ³ PM = 30 mg / m ³	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Operating pressure	NPD	
Electrical safety	NPD	
Total thermal output	54,6 kWh	
Nominal output after elapsed time at 25% of max. mean temperature	P = 3,60 kW	
Flue gas temperature at nominal output	t _a = 140 °C	
Energy efficiency	η = 84,0 %	

The undersigned is responsible for the manufacture and conformity with declared performance



Stian Varre, CEO Nordpeis AS