

DECLARATION OF PERFORMANCE

SalzLBasic-CRP-2017/02/24-GB



PRODUCT

Product type Slow heat release appliance
Type designation Salzburg L Basic; Salzburg L+1 Basic
Product identification See product instruction manual
Intended area of use Heating of rooms in residential buildings
Fuel Wood

MANUFACTURER

Name Nordpeis AS
Adress Gjellebekkstubben 11
3420 Lierskogen, Norway

CHECKS

According to AVCP System 3
Standard EN 15250:2007
Test institute Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625
has checked declared performance and issued test report no. RRF- 50 16 4448

DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1 WT	EN 15250:2007
Minimum distances to combustible material	50 mm rear 300 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion: Carbon monoxide at 13% O ₂ Oxygen nitride NO _x at 13% O ₂ Organic Gaseous Carbon at 13% O ₂ Particulate Matter at 13 O ₂	CO = 0,070 % Vol NO _x = 118 mg / m ³ OGC = 75 mg / m ³ PM = 23 mg / m ³	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Total thermal output	45,14 kWh	
Nominal output after elapsed time at 25% of max. mean temperature	P = 2,00 kW	
Flue gas temperature at nominal output	t _a = 113 °C	
Energy efficiency	η = 90,0 %	

The undersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS